

HD_s3D-1

DepthQ[®]

STEREOSCOPIC



3D projection, by 3D professionals, for professionals who need 3D.



Presenting

The DepthQ[®] HDs3D-1 Stereoscopic Projector



- ⊕ HDMI & VGA Input
- ⊕ 120 Hz page-flip s3D
- ⊕ Up to 2700 ANSI lm in 3D
- ⊕ 1280 x 720/120P
- ⊕ 16.7 million Colors
- ⊕ Factory Warranty:
5 yr. parts¹ - 2 yr. labor²
6 mo. on lamp



Bright. Clear. Precision HDs3D.



Lightspeed Design, Inc.
1611 116th Ave NE, Suite 112
Bellevue, WA 98004, USA
Phone: +1.206.784.1385
www.depthq.com



9.5 in
241 mm

HDs3D-1 FEATURES

- Auto Keystone
- BrilliantColor™
- Built-In Network Services
- ProjectorNet™ 3.0 Ready
- Dust Resistant Design
- HDMI 1.3
- Lens Cap Slider
- LiteTouch™ Touchsense Keypad
- Low Power Standby (<1 W)
- RJ45 Network Connection

2D-Specific Features

- Closed Captioning
- DisplayLink™ Plug & Play
- Dynamic Messaging System (DMS)
- LitePort™ USB JPEG Player
- LiteSwitch™ Instant On/Off
- LiteShow II™ Wireless Ready
- Logo Capture



4.6 in
117 mm

12.4 in
315 mm

Co-developed by
Lightspeed Design, Inc.
and **InFocus Corporation**

Specifications*

3D Native Resolution	WXGA 1280 x 720
Display Technology - DMD	DLP® Technology .65" LVDS DDP2431 with BrilliantColor™
Stereoscopic Compatibility	120 Hz vertical sync page flip active stereo
Delay	8.33 ms (one frame)
Brightness	3D - Up to 2700 ANSI lm depending on configuration 2D - 3500 ANSI lm (2800 lm Eco Mode)
Lamp Life**	4000 Hrs Eco Mode (3000 Hrs Normal)
Contrast Ratio	2100:1 Typical
Audible Noise	30 dB Eco Mode (34 dB High Power)
Computer Compatibility	PC, MAC
Keystone Correction	Automatic, +/-30 degrees
Number of Colors	16.7 Million, True Color
Aspect Ratio	Native 16:9 (4:3, 5:4 Supported)
Lamp Power	280 W
Power Supply	100 ~ 240 Vac, 50/60 Hz
3D Sync - Hor. Scan Freq.	15 - 100 kHz (video/PC)
Vert. Scan Freq.	120 Hz (Video/PC)
Throw Ratio	Approximately 1.5 ~ 1.8
3D Compatibility	WXGA (1280x720), XGA (1024x768), SVGA (800x600)
2D Compatibility	NTSC / NTSC4.43 / PAL / PAL-M / PAL-N / SECAM SDTV: 480i, 576i EDTV: 480p, 576p HDTV: 720p, 1080i, 1080p
Audio	10 W (2 x 5 W)
3D Input Sources	HDMI 1.3 x 1, VGA (HD15) x 2 (only one active at a time)
2D Input Sources	VGA (HD15) x 2, S-Video x 1, Composite Video x 1, DisplayLink™ x 1, HDMI 1.3 x 1, Audio x 4 (3.5 mm x 2, DisplayLink™ x 1, HDMI 1.3 x 1), LitePort™ x 1
Output Sources	VGA (HD15) x 1, Audio x 1 (3.5 mm), Wireless Ready x 1
Control	LAN (RJ45), RS232, DisplayLink™ (USB)
Projection Distance	3.94 ft ~ 32.8 ft / 1.2 m ~ 10 m
Image Offset	15%
Projection Methods	Front, Rear, Ceiling Front, Ceiling Rear
Product Weight	7 lbs / 3.17 kg
Product Dimensions - w-d-h	12.4 x 9.5 x 4.6 in / 315 x 241 x 117 mm
Product Color	Black with Silver trim
Shipping Dimension - w-d-h	16.5 x 12.8 x 9.0 in / 419 x 325 x 229 mm
Shipping Weight	14.3 lbs / 6.48 kg
Maximum Altitude	10,000 ft / 3,000 m
Remote Control	Navigator - 3
Ships With - Accessories	Quick Start Guide, Remote, DVI to HDMI Cable, VGA Cable, USB Cable, Power Cord, Carry Case
Menu Languages	English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Spanish, Traditional Chinese, Simplified Chinese, Swedish, Finnish, Danish, Dutch, Polish, Turkish
Lamp (particle) Containment	Tested to contain particles larger than 0.8 mm ***
Limited Factory Warranty	5 years on parts ¹ - 2 years on labor ² - 6 months on lamp
Accessories Warranty	90 Days
Approvals	C-Tick (Australia), NOM (Mexico), CE (Europe), cMETus (USA & Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore)
Security	Kensington Lock

©2010 Lightspeed Design, Inc. & InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. DepthQ and DepthQ Stereoscopic are registered trademarks of Lightspeed Design, Inc. InFocus is a registered trademark of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies.
¹ Excludes power supply, fans, color wheel and light tunnel which are covered for two (2) years.
² Labour is covered for two (2) years from date of proof of purchase.



* Product availability, specifications, terms, and offerings are subject to change at any time without notice.
** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.
*** Tested to contain particles larger than the specified size in any dimension.